Technical data


4T-842/832


Single row tapered roller bearings



Tapered roller bearing, pressed steel cage

Visual(s)





Product definition

d	82.55 mm
D	168.28 mm
B	56.36 mm
C	41.28 mm
T	53.98 mm
d1	123 mm
a	35.48 mm
e	0.3
Y2	2
Y0	1.1
Mass	5.46 kg
Brand	NTN

Product performance

Dynamic load, C	340 kN
Rating life coefficient, A2	1.4
Static load, C0	460 kN
Fatigue limit load, Cu	52.3 kN
Nlim (oil)	3,000 Tr/min
Nlim (grease)	2,200 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.94 Hz
Characteristic outer ring frequency, BPF0	6.71 Hz
Characteristic inner ring frequency, BPFI	9.29 Hz

Abutment dimensions

ra max	3.5 mm
r1a max	3.3 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If $Po < Fr$, then use $Po = Fr$

The values for e, Y2 and Y0 are shown in the above table