Technical datasheet


4T-H924045

Single row tapered roller bearings



Mounted cone, sheet metal cage

Visual(s)



Product definition

d	111.12 mm
B	52.39 mm
d1	161.5 mm
e	0.67
Y2	0.89
Y0	0.49
Brand	NTN

Product performance

Dynamic load, C	405 kN
Rating life coefficient, A2	1.4
Static load, C0	560 kN
Fatigue limit load, Cu	59 kN
Nlim (oil)	2,000 rpm
Nlim (grease)	1,500 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.41 Hz
Characteristic outer ring frequency, BPF0	7.74 Hz
Characteristic inner ring frequency, BPFI	10.26 Hz

Abutment dimensions

ra max	3.5 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

Po= Xo.Fr + Yo.Fa

X_0	Y_0
0.5	Y0

If Po <Fr, then use Po = Fr

The values for e, Y2 and Y0 are shown in the above table