Technical data


4T-JL819349/JL819310


Single row tapered roller bearings



Tapered roller bearing, pressed steel cage

Visual(s)





Product definition

d	95 mm
D	135 mm
B	20 mm
C	14 mm
T	20 mm
a	30.9 mm
rs min	5 mm
r1s min	2.5 mm
e	0.58
Y2	1.03
Y0	0.57
Mass	0.84 kg
Brand	NTN

Product performance

Dynamic load, C	76.5 kN
Rating life coefficient, A2	1.4
Static load, C0	129 kN
Nlim (oil)	3,000 Tr/min
Nlim (grease)	2,500 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	14.09 Hz
Characteristic outer ring frequency, BPF0	16.35 Hz
Characteristic inner ring frequency, BPFI	18.65 Hz

Abutment dimensions

ra max	5 mm
r1a max	2.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If Po <Fr, then use Po = Fr

The values for e, Y2 and Y0 are shown in the above table