Technical data


4T-JM207049

Single row tapered roller bearings



Mounted cone, sheet metal cage

Visual(s)



Product definition

d	55 mm
B	29 mm
d1	74.5 mm
e	0.33
Y2	1.79
Y0	0.99
Brand	NTN

Product performance

Dynamic load, C	107 kN
Rating life coefficient, A2	1.4
Static load, C0	144 kN
Fatigue limit load, Cu	17.6 kN
Nlim (oil)	5,100 Tr/min
Nlim (grease)	3,800 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	7.22 Hz
Characteristic outer ring frequency, BPF0	8.24 Hz
Characteristic inner ring frequency, BPFI	10.76 Hz

Abutment dimensions

ra max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If Po <Fr, then use Po = Fr

The values for e, Y2 and Y0 are shown in the above table