
Technical data


6303.Z

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, shield on one side

Visual(s)



Product definition

d	17 mm
D	47 mm
B	14 mm
d1	25 mm
D1	40.1 mm
rs min	1 mm
Radial clearance class	CN
Mass	0.11 kg
Brand	SNR

Product performance

Dynamic load, C	13.5 kN
Static load, C0	6.6 kN
Fatigue limit load, Cu	0.3 kN
f0	12.3
Nref	16,000 Tr/min
Nlim	26,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.45 Hz
Characteristic outer ring frequency, BPF0	2.56 Hz
Characteristic inner ring frequency, BPFI	4.44 Hz

Abutment dimensions

da min	22 mm
da max	25 mm
Ce min	0 mm
Da max	42 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr