Technical data


30321U


Single row tapered roller bearings

Tapered roller bearing, pressed steel cage



Visual(s)





Product definition

d	105 mm
D	225 mm
B	49 mm
C	41 mm
T	53.5 mm
a	43.5 mm
rs min	3 mm
r1s min	2.5 mm
e	0.35
Y2	1.74
Y0	0.96
Mass	9.79 kg
ISO 355 reference	T2GB105
Brand	NTN

Product performance

Dynamic load, C	435 kN
Rating life coefficient, A2	1
Static load, C0	530 kN
Nlim (oil)	2,300 Tr/min
Nlim (grease)	1,700 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C

Abutment dimensions

da max	123 mm
db min	132 mm
Da max	211 mm
Db min	209 mm
ra max	3 mm
r1a max	2.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If $Po < Fr$, then use $Po = Fr$

The values for e, Y2 and Y0 are shown in the above table