Technical data


4T-33208


Single row tapered roller bearings



Tapered roller bearing, pressed steel cage

Visual(s)





Product definition

d	40 mm
D	80 mm
B	32 mm
C	25 mm
T	32 mm
d1	60 mm
a	21 mm
rs min	1.5 mm
r1s min	1.5 mm
e	0.36
Y2	1.68
Y0	0.92
Mass	0.73 kg
ISO 355 reference	T2DE040
Brand	NTN

Product performance

Dynamic load, C	103 kN
Rating life coefficient, A2	1.4
Static load, C0	132 kN
Fatigue limit load, Cu	16.1 kN
Nlim (oil)	6,600 Tr/min
Nlim (grease)	4,900 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.81 Hz
Characteristic outer ring frequency, BPF0	7.11 Hz
Characteristic inner ring frequency, BPFI	9.89 Hz

Abutment dimensions

da max	47 mm
db min	48.5 mm
Da min	67 mm
Da max	71.5 mm
Db min	76 mm
Ca min	5 mm
Cb min	7 mm
ra max	1.5 mm
r1a max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa / Fr \leq e$		$Fa / Fr > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If $Po < Fr$, then use $Po = Fr$

The values for e, Y2 and Y0 are shown in the above table