Technical data


4T-47681/47620

Single row tapered roller bearings

Tapered roller bearing, pressed steel cage



Visual(s)



Product definition

d	80.96 mm
D	133.35 mm
B	33.34 mm
C	26.2 mm
T	33.34 mm
d1	108 mm
a	29.44 mm
e	0.4
Y2	1.48
Y0	0.82
Mass	1.78 kg
Brand	NTN

Product performance

Dynamic load, C	153 kN
Rating life coefficient, A2	1.4
Static load, C0	235 kN
Fatigue limit load, Cu	28 kN
Nlim (oil)	3,500 Tr/min
Nlim (grease)	2,600 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.11 Hz
Characteristic outer ring frequency, BPF0	10.74 Hz
Characteristic inner ring frequency, BPFI	13.26 Hz

Abutment dimensions

ra max	3.5 mm
r1a max	3.3 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If Po <Fr, then use Po = Fr

The values for e, Y2 and Y0 are shown in the above table