Technical datasheet


4T-47890

Single row tapered roller bearings

Mounted cone, sheet metal cage



Visual(s)



Product definition

d	92.08 mm
B	34.92 mm
d1	121 mm
e	0.45
Y2	1.34
Y0	0.74
Brand	NTN

Product performance

Dynamic load, C	163 kN
Rating life coefficient, A2	1.4
Static load, C0	266 kN
Fatigue limit load, Cu	30.7 kN
Nlim (oil)	3,100 rpm
Nlim (grease)	2,400 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	10.15 Hz
Characteristic outer ring frequency, BPF0	12.24 Hz
Characteristic inner ring frequency, BPFI	14.76 Hz

Abutment dimensions

ra max	3.5 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

Po= Xo.Fr + Yo.Fa

X_0	Y_0
0.5	Y0

If Po <Fr, then use Po = Fr

The values for e, Y2 and Y0 are shown in the above table