Technical data


4T-782/772


Single row tapered roller bearings



Tapered roller bearing, pressed steel cage

Visual(s)





Product definition

d	104.78 mm
D	180.98 mm
B	48.01 mm
C	38.1 mm
T	47.62 mm
d1	139 mm
a	39.52 mm
e	0.39
Y2	1.56
Y0	0.86
Mass	4.92 kg
Brand	NTN

Product performance

Dynamic load, C	285 kN
Rating life coefficient, A2	1.4
Static load, C0	430 kN
Fatigue limit load, Cu	47.5 kN
Nlim (oil)	2,700 Tr/min
Nlim (grease)	2,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.93 Hz
Characteristic outer ring frequency, BPF0	9.24 Hz
Characteristic inner ring frequency, BPFI	11.76 Hz

Abutment dimensions

ra max	3.5 mm
r1a max	3.3 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If Po <Fr, then use Po = Fr

The values for e, Y2 and Y0 are shown in the above table