Technical data


6307.NR.EE

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, snap ring & groove on outer diameter, contact seals on both sides

Visual(s)



Product definition

d	35 mm
D	80 mm
B	21 mm
d1	46.2 mm
D1	70.1 mm
a min	3.07 mm
a max	3.28 mm
Ca min	4.67 mm
Ca max	4.98 mm
rs min	1.5 mm
rNs min	0.5 mm
D3 max	76.81 mm
b min	1.9 mm
b max	2.2 mm
r0 max	0.6 mm
D4 max	86.6 mm
f	1.65 mm
Snap ring reference	R80
Radial clearance class	CN
Mass	0.45 kg
Brand	SNR

Product performance

Dynamic load, C	33 kN
Static load, C0	19.2 kN
Fatigue limit load, Cu	1.13 kN
f0	13.2
Nlim	6,300 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.07 Hz
Characteristic outer ring frequency, BPF0	3.07 Hz
Characteristic inner ring frequency, BPFI	4.93 Hz

Abutment dimensions

da min	43 mm
da max	46.2 mm
Ce min	0 mm
Da max	72 mm
ra max	1.5 mm
rNa max	0.5 mm
Db min	88 mm