Technical datasheet

7924UCG/GNP42U3G


High precision angular contact ball bearings




High precision angular contact ball bearing, moulded polyamide cage centred on balls

ULTAGE

Visual(s)





Product definition

d	120 mm
D	165 mm
B	22 mm
d1	135.2 mm
d2	131.7 mm
D1	149.8 mm
D2	156.8 mm
a	30.2 mm
Contact angle α	15 °
rs min	1.1 mm
r1s min	0.6 mm
f0	16.6
Precision class	P42
Mass	1.19 kg
Brand	NTN

Product performance

Dynamic load, C	69 kN
Static load, C0	81.5 kN
Nlim (oil)	13,200 rpm
Nlim (grease)	8,200 rpm
Preload level	GN
Preload value	0.41 kN
Axial rigidity	132.4 N/µm
Radial rigidity	770 N/µm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	10.47 Hz
Characteristic outer ring frequency, BPF0	12.72 Hz
Characteristic inner ring frequency, BPFI	15.28 Hz

Abutment dimensions

da min	127 mm
Da max	158 mm
Db max	160.5 mm
r1a max	0.6 mm
ra max	1 mm
D6	135.4 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

Series				e	Single or DT bearing arrangement				DB or DF arrangement			
					Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
					X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)		15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
			0.357	0.4				1.4		1.57		2.28
			0.714	0.43				1.3		1.46		2.11
			1.07	0.46				1.23		1.38		2
			1.43	0.47				1.19		1.34		1.93
			2.14	0.5				1.12		1.26		1.82
			3.57	0.55				1.02		1.14		1.66
			5.35	0.56						1.12		1.63
			7.14	0.56				1		1.12		1.63
		25°		0.68			0.41	0.87		0.92	0.67	1.41
		30°		0.8			0.39	0.76		0.78	0.63	1.24

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

Series			Single or DT bearing arrangement		DB or DF arrangement	
			X_0	Y_0	X_0	Y_0
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)		15°	0.5	0.46	1	0.92
		25°		0.38		0.76
		30°		0.33		0.66

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr