Technical datasheet


NUP.2212.E.G15


Single row cylindrical roller bearings



Single row cylindrical roller bearing, locating, separable, polyamide cage

Visual(s)





Product definition

d	60 mm
D	110 mm
B	28 mm
E	100 mm
F	72 mm
d1	77.5 mm
D1	96.1 mm
rs min	1.5 mm
r1s min	1.5 mm
Radial clearance class	CN
Mass (without HJ ring)	1.12 kg
Brand	SNR

Product performance

Dynamic load, C	127 kN
Static load, C0	150 kN
Fatigue limit load, Cu	18.3 kN
Nref	4,400 rpm
Nlim	7,500 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.98 Hz
Characteristic outer ring frequency, BPF0	6.7 Hz
Characteristic inner ring frequency, BPFI	9.3 Hz

Abutment dimensions

da min	68 mm
dc min	80 mm
Da max	102 mm
ra max	1.5 mm
r1a max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = Fr$

Equivalent static radial load

$Po = Fr$