# Technical data


## 7210.H.G1UJ84

High precision angular contact ball bearings



High precision angular contact ball bearing, laminated resin cage centred on outer ring

## Visual(s)




## Product definition

| | |
|---|---|
| **d** | 50 mm |
| **D** | 90 mm |
| **B** | 20 mm |
| **d1** | 62.45 mm |
| **D1** | 76.85 mm |
| **D2** | 83.87 mm |
| **a** | 26 mm |
| **Contact angle α** | 25 ° |
| **rs min** | 1.1 mm |
| **r1s min** | 0.6 mm |
| **f0** | 14.82 |
| **Precision class** | P4 |
| **Mass** | 0.49 kg |
| **Brand** | SNR |

## Product performance

| | |
|---|---|
| **Dynamic load, C** | 42.8 kN |
| **Static load, C0** | 32.5 kN |
| **Fatigue limit load, Cu** | 1.82 kN |
| **Nlim (oil)** | 21,000 Tr/min |
| **Nlim (grease)** | 13,500 Tr/min |
| **Axial displacement K Factor** | 0.58 |
| **Preload level** | 8 |
| **Preload value** | 1.14 kN |
| **Axial rigidity** | 270 N/µm |
| **Radial rigidity** | 527 N/µm |
| **Min operating temperature, Tmin** | -30 °C |
| **Max operating temperature, Tmax** | 120 °C |
| **Characteristic cage frequency, FTF** | 0.42 Hz |
| **Characteristic rolling element frequency, BSF** | 5.36 Hz |
| **Characteristic outer ring frequency, BPF0** | 6.27 Hz |
| **Characteristic inner ring frequency, BPFI** | 8.73 Hz |

## Abutment dimensions

| | |
|---|---|
| **da min** | 57 mm |
| **db min** | 57 mm |
| **Da max** | 83 mm |
| **Db max** | 83 mm |
| **r1a max** | 0.6 mm |
| **ra max** | 1 mm |
| **D6** | 66.7 mm |

# Calculation factors

**Equivalent dynamic radial load**

P = X.Fr + Y.Fa

| Series | | | | e | Single or DT bearing arrangement | | | | DB or DF arrangement | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | Fa / Fr ≤ e | | Fa / Fr > e | | Fa / Fr ≤ e | | Fa / Fr > e | |
| | | | | | X | Y | X | Y | X | Y | X | Y |
| 70 (NTN & SNR)<br>72 (NTN & SNR)<br>78 (NTN)<br>79 (NTN)<br>719 (SNR) | | 15° | 0.178 | 0.38 | 1 | 0 | 0.44 | 1.47 | 1 | 1.65 | 0.72 | 2.39 |
| | | | 0.357 | 0.4 | | | | 1.4 | | 1.57 | | 2.28 |
| | | | 0.714 | 0.43 | | | | 1.3 | | 1.46 | | 2.11 |
| | | | 1.07 | 0.46 | | | | 1.23 | | 1.38 | | 2 |
| | | | 1.43 | 0.47 | | | | 1.19 | | 1.34 | | 1.93 |
| | | | 2.14 | 0.5 | | | | 1.12 | | 1.26 | | 1.82 |
| | | | 3.57 | 0.55 | | | | 1.02 | | 1.14 | | 1.66 |
| | | | 5.35 | 0.56 | | | | | | 1.12 | | 1.63 |
| | | | 7.14 | 0.56 | | | | 1 | | 1.12 | | 1.63 |
| | | 25° | | 0.68 | | | 0.41 | 0.87 | | 0.92 | 0.67 | 1.41 |
| | | 30° | | 0.8 | | | 0.39 | 0.76 | | 0.78 | 0.63 | 1.24 |

**Equivalent static radial load**

Po = Xo.Fr + Yo.Fa

| Series | | | Single or DT bearing arrangement | | DB or DF arrangement | |
|---|---|---|---|---|---|---|
| | | | $X_0$ | $Y_0$ | $X_0$ | $Y_0$ |
| 70 (NTN & SNR)<br>72 (NTN & SNR)<br>78 (NTN)<br>79 (NTN)<br>719 (SNR) | | 15° | 0.5 | 0.46 | 1 | 0.92 |
| | | 25° | | 0.38 | | 0.76 |
| | | 30° | | 0.33 | | 0.66 |

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr