Technical datasheet


NJ.211.E.G15

Single row cylindrical roller bearings



Single row cylindrical roller bearing, single direction for axial loads, separable, polyamide cage.

Visual(s)



Product definition

d	55 mm
D	100 mm
B	21 mm
E	90 mm
F	66 mm
d1	70.8 mm
D1	86.6 mm
rs min	1.5 mm
r1s min	1.1 mm
Radial clearance class	CN
Mass (without HJ ring)	0.68 kg
Brand	SNR

Product performance

Dynamic load, C	83.1 kN
Static load, C0	94.2 kN
Fatigue limit load, Cu	11.5 kN
Nref	5,800 rpm
Nlim	8,300 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.35 Hz
Characteristic outer ring frequency, BPF0	7.19 Hz
Characteristic inner ring frequency, BPFI	9.81 Hz

Abutment dimensions

da min	63 mm
da max	65 mm
db min	68 mm
dc min	73 mm
Da max	92 mm
ra max	1.5 mm
r1a max	1 mm

Calculation factors

Equivalent dynamic radial load

$P = Fr$

Equivalent static radial load

$P_0 = Fr$