Technical datasheet


NJ.222.E.G15.C3

Single row cylindrical roller bearings



Single row cylindrical roller bearing, single direction for axial loads, separable, polyamide cage.

Visual(s)



Product definition

d	110 mm
D	200 mm
B	38 mm
E	180.5 mm
F	132.5 mm
d1	141.6 mm
D1	173.8 mm
rs min	2.1 mm
r1s min	2.1 mm
Radial clearance class	C3
Mass (without HJ ring)	4.93 kg
Brand	SNR

Product performance

Dynamic load, C	292 kN
Static load, C0	365 kN
Fatigue limit load, Cu	38.9 kN
Nref	3,300 rpm
Nlim	4,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.37 Hz
Characteristic outer ring frequency, BPF0	7.2 Hz
Characteristic inner ring frequency, BPFI	9.8 Hz

Abutment dimensions

da min	121 mm
da max	130 mm
db min	135 mm
dc min	144 mm
Da max	189 mm
ra max	2 mm
r1a max	2 mm

Calculation factors

Equivalent dynamic radial load

$P = Fr$

Equivalent static radial load

$P_0 = Fr$